



AVAILABLE FOR
RENT OR SALE



HP1600WCU TF4 AIR COMPRESSOR

www.atsequipment.com

EPA COMPLIANT PORTABLE AIR COMPRESSOR

Model	HP1600
COMPRESSOR ROTARY SCREW/SINGLE-STAGE	
Free-Air Delivery – cfm	1600
Rated Operating Pressure – psig	150
Pressure Range – psig	80 - 150
Air Discharge Outlet Size – in	3 NPT
Air Discharge Outlet Quantity	1 (2 with IQ)
Fuel Tank Capacity – gal	222.4
ENGINE	
Make/Model	Cummins/QSX15
Emissions Tier Level	Tier 4 Final (T4F)
Number of Cylinders	6
Displacement – cu in	912
Rated Speed – rpm	1800
Idle Speed – rpm	1200
Bhp @ Rated Speed (kW)	580
Electrical - volts	24
Hours of Operation @ Full Load	8.13
DIMENSIONS WITH RUNNING GEAR	
Length – in	292.4
Width – in	90.1
Height – in	99.5
Track Width – in	71
Tire Size – in	17.5
Shipping Weight – w/o fuel – lb	17874
Working Weight – w fuel – lb	19565
DIMENSIONS WITHOUT RUNNING GEAR	
Length – in	228.2
Width – in	90.1
Height – in	98.2
Shipping Weight – w/o fuel – lb	16899
Working Weight – w fuel – lb	18590

Key Features

- Environmentally friendly containment basin offers 110 percent fluid containment, capturing and preventing the spillage of fuel and oil.
- A single-row cooler design encourages easy maintenance and helps ensure high performance in demanding conditions, while a cool-box design prolongs component life and eliminates long cool-down periods.
- Industry-leading service intervals to maximize uptime: Engine oil service needs to be completed only every 500 hours, and airend oil service every 1,000 hours.
- Cummins QSX15 engine delivers both power and efficiency, and is balanced with quiet operation.
- Advanced control system provides easy access to relevant operation and parts manuals, a machine maintenance schedule and spare parts information.
- The full-color, digital display system with LED back-lighting makes machine monitoring easy and efficient.



ATS EQUIPMENT INC. Construction Equipment & Supplies Rentals • Sales • Service

BOSTON, MA
(617) 825-3600

AUBURN, MA
(508) 832-8500

REHOBOTH, MA
(508) 379-6200

CANDIA, NH
(603) 483-2100