DYNAPAC

Part of the Atlas Copco Group

CA2500D

SINGLE-DRUM SOIL COMPACTION ROLLER


AVAILABLE FOR RENT OR SALE



www.atsequipment.com

The 26,230-pound CA2500D single-drum soil compactors features an 84 inch wide drum and two vibration frequencies: 1,740 or 2,160 vpm. It can achieve 50,565 pounds of centrifugal force.

Standard 130-horsepower Cummins QSB4.5engine, vibration-isolated operator's platform, two-speed drive system, and a maintenance-free articulation joint. The CA2500D has a centralized hydraulic test station and comes with a two-year,





60%

ENGINE

Engine / Model Cummins QSB4.5 Cooling Water

Displacement 359 cu. in.
Fuel consumption 4.4 US gal./h
Fuel capacity 72 gal

OPERATING DATA

0		inconcincal gradeaumity, formara	00,0	
Operating weight	26,235 lb	Brakes-front drum/rear axle	disc/disc	
Weight front	12,345 lb	Max compaction depth	39.4"	
Static applied linear drum load	164 lb/in			
Weight, rear	10,362 lb	Vibration	Stage 1	Stage 2
Articulation/oscillation	35/15 degrees	Frequency	1740 vpm	2160 vpm
Turning radius-inside	11'10"	Amplitude	0.063 in	0.024 in
Curb clearance	19.5"	Centrifugal force	50565 lbf	29440 lbf
Drum shell thickness	1.0"	Centrifugal force / drum width	611 lbl/in	356 lbl/in
Travel speed - 1st range	0 - 4.8 mph	Total applied force	64125 lb	43000 lb
- 2nd range	0 - 7.9 mph	Total applied linear force	775 lb	520 lb

Theoretical gradeability, forward

ATS EQUIPMENT INC. Construction Equipment & Supplies Rentals · Sales · Service

BOSTON, MA (617) 825-3600 AUBURN, MA (508) 832-8500 REHOBOTH,MA (508) 379-6200

CANDIA, NH (603) 483-2100