HITACHI ZW120



www.atsequipment.com

WHEEL LOADER



ZW-6 series

98 hp

Engine Power

 $2.0-2.4 \text{ yd}^3$

Bucket ISO Heaped

18,563 lbs

Operating Weight

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service



WHEEL LOADER





www.atsequipment.com

BUCKET DATA			
Bucket Capacity Heaped	(yd³)	2	
Maximum Dumping Clearance	ft-in	8' 10 1/2"	
Dumping Reach	ft-in	3' 3 3/4"	
Bucket Hinge Pin Height	ft-in	11' 8"	
Breakout Force	lbs.	17,760	
Bucket Tilt Back Angle (carry)	degrees	49	
Length	ft-in	21' 3/4"	
Height	ft-in	10' 6 3/8"	
Width (outside tire)	ft-in	7' 5 3/8"	
Width (outside bucket)	ft-in	8' 1/2"	
Wheelbase	ft-in	8' 11 1/4"	
Clearance Circle	ft-in	35' 7 1/2"	
Minimum Ground Clearance	ft-in	1' 2 1/2"	
Full Articulation Angle	degrees	40	
Operating Weight	lbs.	18,563	
Straight Tipping Load	lbs.	14,330	
Full Turn Tipping Load	lbs.	12,367	

_	_	_		
Т		Т	Т	

ENGINE AND TRANSMISSION			
Engine Make/Model		Deutz TCD36	
Horsepower	gross/net	98/95	
Liter Engine	L	3.62	
Number of Cylinders	#	4	
Alternator Amps	amp.	80	
Emission Level	design	Tier 4 Final	
Tier 4 Technology		DOC/SCR	
Transmission Type		Hydrostatic	
Speeds Forward/Reverse	F/R	2F/2R	

SYSTEM FILL CAPACI	TY	
Engine Coolant Capacity (gal)	gal.	4.2
Fuel Tank Capacity (gal)	gal.	27.7
Axle Oil Capacity Front/Rear	gal.	3.7/3.7
Hydraulic Oil Capacity	gal.	13.2

HYDRAULICS/STEER	RING/AXL	ESYSTEMS
Hydraulic Cycle Time	sec.	10.9
Main Hydraulic Pump Type	type	Gear
Differential Gear	type	Limited Slip
Linkage	type	Z Bar
Brake Location		Inboard

Specifications based on ROPS Cab, Counterweight, GP BOCE Bucket,
Material Density of 2800 cu.yds., Operator, Full Fuel and Lubricants, Standard
Tire: 17.5 x 25-12PR (L3). Assembled in Japan.

	m)	-		
ш	m1		(0)	

Tires Std.	17.5 x 25-12PR (L3)
Tires Optional	17.5 R25 (L3)

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service



WHEEL LOADER





ENGINE

Air cleaner, double element

Cold start (glow plug)

Cooler, wide fin

Deutz TCD36 diesel engine

EGR system

Fuel filter (main), w/water separator

Fuel pre-filter, w/water separator

SCR system

Work mode selector

POWERTRAIN

Brakes, service

Enclosed wet disc

Dual system

Inboard mounted

Brake, parking

Spring applied

Oil pressure released

Wet disc type

Differential, torque proportioning (F/R)

Drive shafts, low maintenance

Hydrostatic transmission

Inching pedal

Maximum speed adjuster for 1st speed

Traction control

HYDRAULIC SYSTEM

Boom kick-out, dual (operator adjustable in cab)

Bucket positioner

Control lever, single, pilot-assisted

Control lever lock (electric)

Control valve, 3-spool ready, parallel control

Ride control w/load sensing valve and automatic shut-off

Quick coupler control, lines and controls

Pump, gear, fixed displacement

Steering, orbitrol

ELECTRICAL

24-volt electrical system

Back-up alarm

Battery disconnect switch

Converter, 12V/15 Amp

Horn, dual electric

Instrument panel, LCD, monochrome

Lights:

2 Headlights (halogen)

2 Forward working lights (halogen)

4 Rear working lights (halogen)

2 Stop/tail/backup (LED)

Turn signal w/4-way flashers/marker

CAF

ROPS cab: Enclosed cab with sound suppression, front & rear wipers and washers, two rear view and side mirrors, tinted glass, full view latch-back doors, sliding side windows.

Accessory outlet, 12V,

Adjustable armrest/console, (fore/aft sliding)

Air conditioner/heater/pressurizer

AM/FM/WB radio with AUX input

Ashtray

Cab dome lamps (2)

Cigarette lighter

Coat hook

Cooler box storage area

Cup holder (2)

Floormat

Retractable seat belt (3 inch)

ROPS/FOPS certified

Seat, air suspension, fabric

Steering column, telescoping and tilting

w/quick-release pedal

Storage box (heated/cooled)

Sun visor

OTHERS

Articulation locking bar

Counterweight

Drawbar

Global e-Service, telematic monitoring system

(GSM-version w/4 yrs. service)

Ladders, inclined

Lifting eyes

Linkage pins, HN bushing

Neutral safety start

Steps, rear
Z-bar loader linkage

ALARMS, GAUGES, INDICATORS

Engine coolant temperature

Alarms (visual & Engine oil low pressure Engine oil low pressure Overheat (engine coolant)

Fuel gauge

Gauges

Indicators

HST oil temperature
Air cleaner element

Air conditioner display

Battery discharge warning

Cold start

Control lever lock

Eco-operating status

Emergency steering

Engine warning

Fan reverse rotation

Fuel filter (water in fuel)

High beam

HST oil temperature

HST warning

Maintenance

Operating mode (Normal, Power)

Parking brake

Ride control

Service Speedometer

Time/operating hour/ODO

Turn signal w/4-way flashers/marker

Work light

OPTIONAL EQUIPMENT

Belly guard, transmission

Bolt-on cutting edge & segments

Camera, rear view

Fenders, rear, full, w/mudflap

HID work lights

High lift boom arm

Hydraulic system, 3 spool valve

I FD work lights

Pre-cleaner (turbine type)

Quick coupler & attachments

Seat, heated

Secondary steering

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service

BOSTON, MA (617) 825-3600 AUBURN, MA (508) 832-8500 REHOBOTH,MA (508) 379-6200 CANDIA, NH (603) 483-2100