



www.atsequipment.com

WHEEL LOADER



ZW-6 series

138 hp Engine Power 3.1–3.5 yd³

27,006 lbs

Bucket ISO Heaped

Operating Weight

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service



WHEEL LOADER

Full Turn Tipping Load





www.atsequipment.com

BUCKET DATA		
Bucket Capacity Heaped	(yd³)	3.1
Maximum Dumping Clearance	ft-in	9' 2 5/8"
Dumping Reach	ft-in	3' 5"
Bucket Hinge Pin Height	ft-in	12' 7"
Breakout Force	lbs.	21,604
Bucket Tilt Back Angle (carry)	degrees	50
Length	ft-in	24' 6"
Height	ft-in	10' 8 1/2"
Width (outside tire)	ft-in	8' 1"
Width (outside bucket)	ft-in	8' 4 3/4"
Wheelbase	ft-in	9' 101/8"
Clearance Circle	ft-in	39' 6"
Minimum Ground Clearance	ft-in	1' 5"
Full Articulation Angle	degrees	40
Operating Weight	lbs.	27,006
Straight Tipping Load	lbs.	22,531

ENGINE AND TRANSMISSION

Engine Make/Model		Cummins QSB4.
Horsepower	gross/net	139/138
Liter Engine	L	5.193
Number of Cylinders	#	4
Alternator Amps	amp.	50
Emission Level	design	Tier 4 Final
Tier 4 Technology		DOC/SCR
Transmission Type		Hydrostatic
Speeds Forward/Reverse	F/R	4F/4R

SYSTEM FILL CAPACITY

Engine Coolant Capacity (gal)	gal.	6.3
Fuel Tank Capacity (gal)	gal.	50
Axle Oil Capacity Front/Rear	gal.	6.6/6.6
Hydraulic Oil Capacity	gal.	21.1

HYDRAULICS/STEERING/AXLE SYSTEMS

Hydraulic Cycle Time	sec.	11.9
Main Hydraulic Pump Type	type	Gear
Differential Gear	type	Limited Slip
Linkage	type	Parallel
Brake Location		Inhoard

TIRES

 Tires Std.
 20.5-25 12PR (L2)

 Tires Optional
 20.5-R25 (L3)

Specifications based on ROPS Cab, Counterweight, GP BOCE Bucket, Material Density of 2800 cu.yds., Operator, Full Fuel and Lubricants, Standard Tire:20.5-25 12PR (L2). Assembled in Japan.

lbs.

19,532

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service



WHEEL LOADER





STANDARD EQUIPMENT

ENGINE
Air cleaner, double element
Auto idle shut down
Cold start (glow plug)
Cooling fan, automatic reversible
Cummins QSB4.5 diesel engine
Diesel particulate filter (exhaust filter)
EGR system
Fuel filter (main), w/water separator
Fuel pre-filter, w/water separator
VGT (Variable Geometry Turbocharger)
Work mode selector

HYDRAULIC SYSTEM

Quick coupler control lines and controls Ride control w/load sensing valve and automatic

Universal joints, sealed

Bucket positioner
Quick coupler control lines and controls
Control Lever, single, pilot-assisted w/1 aux Lever for 3rd spool control
Control lever lock (electric)
Control valve, 3-spool, parallel control
Pump, goar fixed displacement

Boom kick-out, dual (operator adjustable in cab)

shut-off	
Steering, orbitrol	

LLLOTTIOAL
24-volt electrical system
Back-up alarm
Batteries (2), 12V, 565 CCA
Battery disconnect switch
Converter, 12V/15 Amp
Horn, dual electric
Instrument panel, LCD, monochrome
Lights:
2 Headlights (halogen)
2 Forward working lights (halogen)
4 Rear working lights (halogen)

FLECTRICAL

2 Stop/tail/backup (LED) Turn signal w/4-way flashers/marker

JAB .	
ROPS cab: Enclosed cab with sound suppression, front & rear wipers and washers, two rear view and sic mirrors, tinted glass, full view latch-back doors, sliding side windows.	
Accessory outlet, 12V,	
Adjustable armrest/console, (fore/aft sliding)	

Air conditioner/heater/pressurizer
AM/FM/WB radio with AUX input
Ashtray
Cab dome lamps (2)
Cigarette lighter
Coat hook
Cooler box storage area
Cup holder (2)
Floormat
Retractable seat belt (3 inch)
ROPS/FOPS certified

Seat, air suspension, fabric	
Steering column, telescoping and tilting w/quick-release pedal	
Storage box (heated/cooled)	

OTHERS

Articulation locking bar

Sun visor

Counterweight
Drawbar
Fenders, front, w/mudflap
Fenders, rear, deck-type, w/mudflap
Global e-Service, telematic monitoring system (GSM-version w/4 yrs. service)
Ladders, inclined
Lifting eyes
Linkage pins, HN bushing
Neutral safety start
Rear grill, steel
Steps, rear
Vandalism protection
Z-bar loader linkage

ALARMS, GAUGES, INDICATORS

Brake oil low pressure
Engine oil low pressure
Hydraulic oil level
Overheat (engine coolant)
Steering oil low pressure
Engine coolant temperature
Fuel gauge
HST oil temperature
Air cleaner element
Air conditioner display
Battery discharge warning
Cold start
Control lever lock
Diesel particulate filter status
Eco-operating status
Emergency steering
Engine warning
Fan reverse rotation
F-N-R selection
F-N-R switch enable
Fuel filter (plugged filter)
Fuel filter (water in fuel)
High beam
HST oil temperature
HST warning
Maintenance
Operating mode (Normal, Power)
Parking brake
Ride control
Service
Speedometer
Time/operating hour/ODO
Turn signal w/4-way flashers/marker

Work light

OPTIONAL EQUIPMENT
Belly guard, transmission
Bolt-on cutting edge & segments
Bucket teeth
Camera, rear view
Dual lever hydraulic control
Fenders, rear, full, w/mudflap
HID work lights
High lift boom arm
Hydraulic system, 3 spool valve
LED work lights
Pre-cleaner (turbine type)
Quick coupler & attachments
Quick coupler, full cast

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service

BOSTON, MA (617) 825-3600

AUBURN, MA (508) 832-8500

REHOBOTH, MA (508) 379-6200

CANDIA, NH (603) 483-2100