

www.atsequipment.com

HITACHI **ZW220**



ZW-6 series

193 hp Engine Power **4.2–4.7 yd³** Bucket ISO Heaped **38,910 lbs** Operating Weight

| ATS EQUIPMENT INC. | Construction Equipment & Supplies | | Rentals · Sales · Service | |
|--------------------|--|----------------|----------------------------------|--|
| BOSTON, MA | AUBURN, MA | REHOBOTH,MA | CANDIA, NH | |
| (617) 825-3600 | (508) 832-8500 | (508) 379-6200 | (603) 483-2100 | |





BUCKET DATA

| Bucket Capacity Heaped | (yd³) | 4.2 |
|--------------------------------|---------|------------|
| Maximum Dumping Clearance | ft-in | 9' 5 3/4" |
| Dumping Reach | ft-in | 3' 8 1/2" |
| Bucket Hinge Pin Height | ft-in | 13' 5" |
| Breakout Force | lbs. | 34,170 |
| Bucket Tilt Back Angle (carry) | degrees | 50 |
| Length | ft-in | 27' 3 1/8" |
| Height | ft-in | 11' 7/8" |
| Width (outside tire) | ft-in | 9' 1 5/8" |
| Width (outside bucket) | ft-in | 9' 6 1/2" |
| Wheelbase | ft-in | 10' 9 7/8" |
| Clearance Circle | ft-in | 45' 8" |
| Minimum Ground Clearance | ft-in | 1' 5 3/4" |
| Full Articulation Angle | degrees | 37 |
| Operating Weight | lbs. | 38,910 |
| Straight Tipping Load | lbs. | 32,850 |
| Full Turn Tipping Load | lbs. | 29,100 |

Specifications based on ROPS Cab, Counterweight, GP BOCE Bucket, Material Density of 2800 cu.yds., Operator, Full Fuel and Lubricants, Standard Tire: 26.5-25 16PR (L-3). Assembled in the U.S.

| ENGINE AND TRANSM | NISSION | |
|-------------------------------|----------------|----------------|
| Engine Make/Model | | Cummins QSB6.7 |
| Horsepower | gross/net | 200/193 |
| Liter Engine | L | 6.69 |
| Number of Cylinders | # | 6 |
| Alternator Amps | amp. | 65 |
| Emission Level | design | Tier 4 Final |
| Tier 4 Technology | | DOC/SCR |
| Transmission Type | | Countershaft |
| Speeds Forward/Reverse | F/R | 5F/3R |
| | | |
| SYSTEM FILL CAPAC | ITY | |
| Engine Coolant Capacity (gal) | gal. | 7.9 |
| Fuel Tank Capacity (gal) | gal. | 67.4 |
| Axle Oil Capacity Front/Rear | gal. | 8.5/8.5 |
| | | |

| Hydraulic Oil Capacity | gal. | 30.1 |
|--------------------------|-----------|--------------|
| HYDRAULICS/STEERIN | NG/AXLE S | SYSTEMS |
| Hydraulic Cycle Time | Sec. | 10.4 |
| Main Hydraulic Pump Type | type | Piston |
| Differential Gear | type | Limited Slip |
| Linkage | type | Z Bar |
| Brake Location | | Inboard |

TIRES

Tires Std. Tires Optional 23.5-25 16PR (L-3) 23.5R25 (L-3)

ATS EQUIPMENT INC. Construction Equipment & Supplies Rentals · Sales · Service

BOSTON, MA (617) 825-3600 AUBURN, MA (508) 832-8500 REHOBOTH,MA (508) 379-6200 CANDIA, NH (603) 483-2100

HITACHI ZW220

WHEEL LOADER

STANDARD EQUIPMENT

ENGINE

| Air cleaner, double element |
|---|
| Auto idle shut down |
| Cold start (intake air heater) |
| Cooling fan, automatic reversible, swing-out type |
| Cummins QSB6.7 diesel engine |
| EGR System |
| Engine block heater 120V |
| Fuel filter (Main) |
| Fuel pre-filter, w/water separator |
| Rain cap |
| SCR catalyst and DOC |
| VGT (variable geometry turbocharger) |
| Work mode selector |

POWERTRAIN

| Brakes, service |
|---|
| Enclosed wet disc |
| Dual system |
| Inboard mounted |
| Brake, parking |
| Spring applied |
| Oil pressure released |
| Dry disc type |
| Differential, limited slip type (F/R) |
| Down-shift switch |
| Drive shafts, low maintenance |
| F-R direction selector (2-column mounted/ console mounted) |
| 1st speed hold switch on side console |
| Quick Power switch |
| Transmission, automatic w/load sensing system. |
| Transmission declutch (3-position L/H/Off) |
| Transmission mode selection (3-position AUTO1/MAN/ AUTO2) |
| Universal joints, sealed |
| |

HYDRAULIC SYSTEM

| Boom kick-out, dual (operator adjustable in cab) |
|--|
| Bucket positioner (horizontal) |
| Control lever, single, pilot-assisted |
| Control lever lock (electric) |
| Control valve, 3-spool, parallel and tandem control |
| Pump, variable displacement, load-sensing |
| Ride control w/load sensing valve and automatic shut-off |
| Quick coupler control lines and controls |
| Steering, pilot |
| System; open-center, high-pressure, load-sensing |
| Valve, anti-drift |
| |

| ELECTRICAL |
|-------------------------------------|
| 24-volt electrical system |
| Back-up alarm |
| Batteries (2), 12V, 1,000 CCA |
| Battery disconnect switch |
| Camera, rear-view |
| Converter, 12V/15 Amp |
| Horn, dual electric |
| Instrument panel, LCD, color |
| Lights: |
| 2 Headlights (halogen) |
| 2 Forward working lights (halogen) |
| 4 Rear working lights (halogen) |
| 2 Stop/tail/backup (LED) |
| Turn signal w/4-way flashers/marker |

CAB

| ROPS cab: enclosed cab with sound suppression, ront & rear wipers and washers, two rear view and nirrors, tinted glass, full view latch-back doors, slid ide windows. | |
|--|--|
| Accessory outlet, 12v | |
| Adjustable armrest/console, (fore/aft sliding) | |
| Air conditioner/heater/pressurizer | |
| M/FM/WB radio with AUX input | |
| Ashtray | |
| Cab dome lamps (2) | |
| Digarette lighter, 24V | |
| Coat hook | |
| Cup holder (2) | |
| Floormat, sweep-out | |
| Prepped for Loadrite Scale | |
| Retractable seat belt (3-inch) | |
| ROPS/FOPS certified | |
| Seat, deluxe heated w/TLV suspension (DLX8500) | |
| Steering column, telescoping and tilting v/quick-release pedal | |
| Steering wheel | |
| Storage box (heated/cooled) | |
| Storage tray | |
| Sun visor | |
| | |

OTHERS

| UTHERS |
|--|
| Articulation locking bar |
| Counterweight |
| Drawbar |
| Fenders, front, w/mudflap |
| Fenders, rear, deck-type, w/mudflap |
| KCM Global e-service, telematic monitoring system (GSM-version w/4 yrs. service) |
| Ladders, inclined |
| Lifting eyes |
| Linkage pins, HN bushing |
| Neutral safety start |
| Rear grill, hinged |
| Steps, rear |
| Vandalism protection |
| Z-bar loader linkage |

AVAILABLE FOR RENT OR SALE



ALARMS, GAUGES, INDICATORS Alarms (visual & Aftertreatment device Aftertreatment device regeneration audible) system Air cleaner element Axle oil temperature Battery discharge warning Brake oil low pressure CAN network system DEF/AdBlue tank level/quality/system Engine oil low pressure Engine trouble Engine warning Fuel filter (water in fuel) Hydraulic oil level Hydraulic oil temperature Main pump oil pressure Overheat (engine coolant) Transmission oil temp Transmission warning Gauges DEF/AdBlue tank level Engine coolant temperature Fuel gauge Speedometer Tachometer Transmission oil temperature Indicators Aftertreatment device regeneration Air conditioner display Boom kick-out, dual Cold start Control lever lock Declutch ECO-Operating Status Fan reverse rotation F-N-R Selection F-N-R Switch enable High beam Parking brake Shift hold Time/Operating hour/ODO Transmission mode and status Turn signal w/4-way flashers/Marker Work light Work mode (Normal, Power)

OPTIONAL EQUIPMENT Autolube Belly guard, transmission Bolt-on cutting edge & segments Bucket teeth Counterweight, refuse Dual lever hydraulic control E-stick steering Fenders, rear, full w/mudflaps HID work lights High lift boom arm Hydraulic system, 3 spool valve LED work lights Quick coupler & attachments

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service

BOSTON, MA (617) 825-3600 AUBURN, MA (508) 832-8500 REHOBOTH,MA (508) 379-6200 CANDIA, NH (603) 483-2100