HITACHI ZW310



www.atsequipment.com

WHEEL LOADER



ZW-6 series

272 hpEngine Power

5.5–6.1 yd³
Bucket ISO Heaped

53,200 lbs

Operating Weight

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service



WHEEL LOADER





www.atsequipment.com

| BUCKET DATA | | |
|--------------------------------|---------|------------|
| Bucket Capacity Heaped | (yd³) | 5.5 |
| Maximum Dumping Clearance | ft-in | 10' 1 7/8" |
| Dumping Reach | ft-in | 4' 3 5/8" |
| Bucket Hinge Pin Height | ft-in | 14' 6 1/4" |
| Breakout Force | lbs. | 44,740 |
| Bucket Tilt Back Angle (carry) | degrees | 50 |
| Length | ft-in | 29' 7 3/8" |
| Height | ft-in | 11' 7" |
| Width (outside tire) | ft-in | 9' 7 3/8" |
| Width (outside bucket) | ft-in | 10' 2" |
| Wheelbase | ft-in | 11' 3 7/8" |
| Clearance Circle | ft-in | 48' 1 1/2" |
| Minimum Ground Clearance | ft-in | 1' 7 7/8" |
| Full Articulation Angle | degrees | 37 |
| Operating Weight | lbs. | 53,200 |
| Straight Tipping Load | lbs. | 41,490 |
| Full Turn Tipping Load | lbs. | 36,180 |

| | | ı |
|--|--|---|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

| ENGINE AND TRANSM | ISSION | |
|------------------------|-----------|--------------|
| Engine Make/Model | | Cummins QSL9 |
| Horsepower | gross/net | 286/272 |
| Liter Engine | L | 8.9 |
| Number of Cylinders | # | 6 |
| Alternator Amps | amp. | 95 |
| Emission Level | design | Tier 4 Final |
| Tier 4 Technology | | SCR |
| Transmission Type | | Countershaft |
| Speeds Forward/Reverse | F/R | 4F/4R |
| | | |

| SYSTEM FILL CAPACI | TY | |
|-------------------------------|------|-----------|
| Engine Coolant Capacity (gal) | gal. | 12.4 |
| Fuel Tank Capacity (gal) | gal. | 99 |
| Axle Oil Capacity Front/Rear | gal. | 12.7/12.7 |
| Hydraulic Oil Capacity | gal. | 36.2 |

| HYDRAULICS/STEER | RING/AXL | ESYSTEMS |
|--------------------------|----------|--------------|
| Hydraulic Cycle Time | sec. | 10.9 |
| Main Hydraulic Pump Type | type | Piston |
| Differential Gear | type | Torque Prop. |
| Linkage | type | Z Bar |
| Brake Location | | Inboard |

| Specifications based on ROPS Cab, Counterweight, GP BOCE Bucket, Mate- |
|--|
| rial Density of 2800 cu.yds., Operator, Full Fuel and Lubricants, Standard Tire: |
| 26.5-R25 // 3). Assembled in the LLS |

| TINES | |
|----------------|---------------------|
| Tires Std. | 26.5-R25 (L3) |
| Tires Optional | 26.5 25 20PR (L3-5) |

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service



WHEEL LOADER





STANDARD EQUIPMENT

Work mode selector

| ENGINE |
|--------------------------------------|
| Air cleaner, double element |
| Auto idle shut down |
| Cold start (intake air heater) |
| Cooling fan, automatic reversible |
| Cummins QSL9 diesel engine |
| EGR System |
| Engine block heater 120V |
| Fuel filter (Main) |
| Fuel pre-filter, w/water separator |
| Rain cap |
| SCR catalyst and DOC |
| VGT (variable geometry turbocharger) |

| POWERTRAIN |
|---|
| Brakes, service |
| Enclosed wet disc |
| Dual system |
| Inboard mounted |
| Brake, parking |
| Spring applied |
| Oil pressure released |
| Wet disc type |
| Differential, torque proportioning type (F/R) |
| Down-shift switch |
| Drive shafts, low maintenance |
| F-R direction selector (2-column mounted/ console mounted) |
| Lock-up torque converter |
| Quick Power switch |
| Transmission, automatic w/load sensing system. |
| |

Universal joints, sealed

Transmission declutch (3-position L/H/Off)

HYDRAULIC SYSTEM Boom kick-out, dual (operator adjustable in cab) Bucket positioner (horizontal) Control lever, dual, pilot-assisted Control lever lock (electric) Control valve, 2-spool, parallel and tandem control

Transmission mode selection (3-position AUTO1/MAN/

Pump, variable displacement, load-sensing Ride control w/load sensing valve and automatic

shut-off

Steering, pilot

System; open-center, high-pressure, load-sensing

Valve, anti-drift

ELECTRICAL

24-volt electrical system Back-up alarm Batteries (2), 12V, 1,000 CCA Battery disconnect switch Camera, rear-view Converter, 12V/15 Amp Horn, dual electric Instrument panel, LCD, color

2 Headlights (halogen)

2 Forward working lights (halogen) 4 Rear working lights (halogen)

2 Stop/tail/backup (LED)

Turn signal w/4-way flashers/marker

CAB

ROPS cab: enclosed cab with sound suppression, front & rear wipers and washers, two rear view and side mirrors, tinted glass, full view latch-back doors, sliding

Accessory outlet, 12v Adjustable armrest/console, (fore/aft sliding) Air conditioner/heater/pressurizer AM/FM/WB radio with AUX input

Ashtray Cab dome lamps (2)

Cigarette lighter, 24V Coat hook

Floormat, sweep-out Prepped for Loadrite Scale

Retractable seat belt (3-inch) ROPS/FOPS certified

Seat, deluxe heated w/TLV suspension (DLX8500)

Steering column, telescoping and tilting

Steering wheel

Storage box (heated/cooled)

Storage tray Sun visor

OTHERS

Articulation locking bar

Counterweight

Drawbar

Fenders, front, w/mudflap

Global e-service, telematic monitoring system

(GSM-version w/4 yrs. service)

Lifting eyes

Linkage pins, HN bushing

Neutral safety start Rear grill, hinged

Steps, rear Vandalism protection

Z-bar loader linkage

ALARMS, GAUGES, INDICATORS

(visual & Aftertreatment device regeneration Air cleaner element Axle oil temperature Battery discharge warning Brake oil low pressure CAN network system DEF/AdBlue tank level/quality/system Engine oil low pressure Engine trouble Engine warning Fuel filter (water in fuel) Hydraulic oil level Hydraulic oil temperature Main pump oil pressure Overheat (engine coolant) Transmission oil temp Transmission warning Gauges DEF/AdBlue tank level Engine coolant temperature Fuel gauge Tachometer Transmission oil temperature Indicators Aftertreatment device regeneration Air conditioner display Boom kick-out, dual Cold start Control lever lock Declutch ECO-Operating Status Fan reverse rotation F-N-R Selection F-N-R Switch enable

OPTIONAL EQUIPMENT

Work light

High beam

Parking brake

Time/Operating hour/ODO

Transmission mode and status

Work mode (Normal, Power)

Turn signal w/4-way flashers/Marker

Autolube

Belly guard, transmission

Bolt-on cutting edge & segments

Bucket teeth

Counterweight, optional

High lift boom arm

Hydraulic system, 3 spool valve

LED work lights

Quick coupler & attachments

Single lever hydraulic control w/multifunction grip

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service