

Construction Equipment & Supplies Rentals · Sales · Service

BOSTON, MA (617) 825-3600

AUBURN, MA (508) 832-8500

REHOBOTH, MA (508) 379-6200

CANDIA, NH (603) 483-2100

www.atsequipment.com

Ð

Limited Warranty:

Not for use in residential
Iving areas or inadequately ventilated areas
Proper ventilation required during operation

1 Year Important Notes

Propane Tank-Top Radiant

For convenient, versatile radiant heat, these propane tank-top heaters are great for outdoor use. Just connect to a standard 20 pound propane cylinder for up to 48 hours of heating.



- Heavy-duty construction
- Rust-proof chrome emitter guard ✓ Rear burner safety guard

Heat Output

- ✓ Variable heat control valve
- Clean, quiet, instant radiant heat
- Components
- Standard propane tank connection
- High efficiency heat reflector
- ✓ Hand wheel connection for valve



MH-0030-IM10

For use in open workshops, construction sites, farms and for any other outdoor heating need.

MODEL NUMBER	MH-0015-IM10	MH-0030-IM10
HEAT OUTPUT (SINGLE BURNER)*	L-9,000 / M-12,000 / H-16,000 BTU	L-9,000 / M-12,000 / H-16,000 BTU
HEAT OUTPUT (DOUBLE BURNER)*	N/A	L-18,000 / M-24,000 / H-32,000 BTU
IGNITION TYPE	Match light	Match light
HEAT SETTINGS	3	6
PROPANE CYLINDER SIZE	20 lb.	20 lb.
MAX. OPERATING HOURS (20 LB. CYL)*	L-48 / M-36 / H-27 hours	L-48 / M-18 / H-14 hours
SWIVEL BURNER HEAD	No	Yes
SAFETY SHUT-OFF VALVE	Yes	Yes
HEAT REGULATOR KNOB	Yes	Yes
MANIFOLD	Cast aluminum	Cast aluminum
DIMENSIONS (LxWxH)	8.4x7.4x12in.	17.5x5.5x12in.
SHIP WT.	3 lb.	6 lb.
NET WT.	2 lb.	5 lb.

To see more online, scan here or go to www.mitm.com:



*Heat output and operating hours are at Low, Medium and High settings

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.