

SJ6832 RT ROUGH TERRAIN SCISSOR



32' MINI ROUGH TERRAIN DUAL FUEL AND DIESEL

SUPERIOR GRADEABILITY

Skyjack rough terrain scissor lifts boast impressive platform capacities and industry-leading gradeability (up to 50%). With crossover symmetrical four-wheel drive, these machines deliver maximum torque to all wheels for superior all terrain performance.

SKYCODED™

A proven and reliable control system, incorporating Skyjack's color coded and numbered wiring system, make our machines the easiest to trouble shoot and repair which means easier maintenance and lowered costs.

STANDARD FEATURES

- Crossover symmetrical 4WD
- Drivable at full height with roll out deck fully extended
- Shroud style, impact resistant composite control box with extended cable
- 5′ (1.52 m) Roll out extension deck
- Dual fuel (gas/propane) or diesel engine
- 90° Swing out engine tray
- Multiple wet disc spring applied hydraulic release brakes
- 110V AC Outlet on platform with GFI
- Up to 50% gradeability
- Foam-filled low profile grip lug tires
- Tilt alarm with drive & lift cut-out
- Tilt sensor (4.5° x 2.5°)
- Lanyard attachment points
- All motion audible alarm
- Operator horn
- Hinged railing system



- Forklift pockets and tie down / lift lugs
- Overload sensing system
- Fold down hinged railing system
- Full height spring hinged entry gate at rear of unit
- SKYCODED™ Color coded and numbered wiring system
- Telematics ready
- 2-Year Gold Leaf Warranty (5-year structural warranty)
- † Standard lead times may be increased when optional equipment is added, consult factory.
- \ddagger Capacities and machine weights may differ when options are added.

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service



SJ6832 RT SCISSOR


32' MINI ROUGH TERRAIN DUAL FUEL AND DIESEL






www.atsequipment.com

Dimensions	SJ6832 RT
A Work Height	38'
B Raised Platform Height	32'
C Lowered Platform Height	54"
D Overall Width	69.5"
E Overall Length	107"
F Stowed Height (Rails Up)	99"
G Stowed Height (Rails Down)	69"
H Platform Width (Inside Dimension)	56"
Platform Length (Inside Dimension)	96"
Specifications	SJ6832 RT
Extension Deck	5'
Ground Clearance	8"
Wheelbase	80.5"
Weight	7,590 lbs
Gradeability	40%
Turning Radius (Inside)	60"
Turning Radius (Outside)	156"
Lift Time (With Rated Load)	39 sec
Lower time (With Rated Load)	36 sec
Drive Speed (Stowed)	3.8 mph
Drive Speed (Raised)	0.4 mph
Maximum Drive Height	Full Height
Capacity (Overall)	1,000 lbs
Distributed Capacity (Main Platform)	700 lbs
Distributed Capacity (Extension Deck)	300 lbs
Local Floor Load (With Rated Load)	216 psi
Overall Floor Load (With Rated Load)	200 psf
Maximum # of persons up to 28 mph (12.5 m/s) wind rating	4
Diesel Engine	24.8 HP Kubota
Fuel Tank	23 gal
Hydraulic Reservoir	23 gal
Outrigger Leveling (Front to Back / Side to Side)	5° / 8°
Tire Type	Foam-Filled
Tire Size	26 x 12





ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service

BOSTON, MA (617) 825-3600 AUBURN, MA (508) 832-8500

REHOBOTH,MA (508) 379-6200 CANDIA, NH (603) 483-2100