

# ICS 890F4

### **AVAILABLE FOR RENT OR SALE**



www.atsequipment.com

## **HYDRAULIC CHAIN SAW**











### 890F4/PG

#### A Great Saw with a Bad Attitude

If you're looking for the highest level of performance and cutting capability, look no further. The 890PG hydraulic utility chain saw offers cutting depths up to 25" in ductile iron, cast iron, PVC, HDPE, Insituform lining and even Asbestos\* concrete pipe. The deep cutting ability of the 890F4 with PowerGrit® Utility chain, allows the operator to make a single cut from one side meaning less excavation is required. Change the way you cut pipe! Also the 890PG is capableof operating the full line of 890Series concrete cutting chains, meaning you can usse the saw on masonry, stone and even reinforced concrete - perfect for pipe taps, utility vaults, bridge work and other utility applications.

\* Asbestos is a hazardous material, known to cause serious respiratory diseases. Cutting into asbestos can release asbestos fibers into the air. Always research and follow the correct safety procedures, including applicable national and state or provisional occupational health and safety regulations, and protect yourself and those around you from asbestos-related disease. Always arrange for the material to be removed safely by a qualified person. ICS is not responsible for exposure to asbestos caused by use of this product.

| 890F4/PG PRODUCT SPECIFICATIONS - 8 GPM / 12 GPM |   |
|--|---|
| WEIGHT   | 27.3 lbs/12.4 kg with                       |
|  | 15-inch (38 cm) bar and chain               |
| BAR LENGTH                                       | Up to 25" (63 cm)                           |
| MOTOR SPEED                                      | 6100 / 6400 rpm                             |
| POWERHEAD  | 23" L x 10.5" H x 9.5" W                    |
| DIMENSIONS                                       | (58.5 cm x 26.5 cm x 24 cm)                 |
| TORQUE   | 122 / 172 in-lbs                            |
| HORSEPOWER                                       | 11.5 / 17.5 hp                              |
| HYDRAULIC  | 8 / 12 gpm (30 / 45 lpm)                    |
| SUPPLY   | 2500 psi (172.5 bar)                        |
| NOISE LEVEL                                      | 88 dB @ 3 ft (1 m)                          |
| VIBRATION LEVEL                                  | 4 meters/second <sup>2</sup> (front handle) |
| WATER SUPPLY                                     | Minimum 20 psi (1.5 bar)                    |
| D 1 1 1 1  |   |

 Product data shown is rated based on maximum input conditions and efficiency assumptions and may vary dependent on power supply.

ATS EQUIPMENT INC. Construction Equipment & Supplies Rentals • Sales • Service