



Doosan Portable Power XP1000 HP915 Spec Sheet



| Model | XP1000 | HP915 |
|---|--------------------------|--------------------------|
| COMPRESSOR ROTARY SCREW/SINGLE-STAGE | | |
| Free-Air Delivery – cfm (m3/min) | 1000 (28.3) | 915 (25.9) |
| Rated Operating Pressure – psig (bar) | 125 (8.6) | 150 (10.3) |
| Pressure Range – psig (bar) | 80 - 150 (5.5 - 10.3) | 80 - 175 (5.5 - 12.1) |
| Air Discharge Outlet Size – in (mm) | 2-inch NPT (50.8) | |
| Air Discharge Outlet Quantity | 1 | |
| Fuel Tank Capacity – gal (L) | 128 (485) | |
| ENGINE | | |
| Make/Model | Cummins/QLS9 | |
| Emissions Tier Level | Tier 4 Final (T4F) | |
| Number of Cylinders | 6 | |
| Displacement – cu in (L) | 543 (8.9) | |
| Rated Speed – rpm | 1800 | |
| Idle Speed – rpm | 1200 | |
| Bhp @ Rated Speed (kW) | 303 (226) | |
| Electrical - volts | 24 | |
| Hours of Operation @ Full Load | 8.7 | |
| DIMENSIONS WITH RUNNING GEAR | | |
| Length – in (mm) | 226.6 (5748) | |
| Width – in (mm) | 82.6 (2098) | |
| Height – in (mm) | 101.3 (2573) | |
| Track Width – in (mm) | 69.3 (1760) | |
| Tire Size – in | 16 | |
| Shipping Weight – w/o fuel – lb (kg) | 10461 (4745) | |
| Working Weight – w fuel – lb (kg) | 11309 (5130) | |
| DIMENSIONS WITHOUT RUNNING GEAR | | |
| Length – in (mm) | 171 (4343) | |
| Width – in (mm) | 83 (2108) | |
| Height – in (mm) | 95 (2413) | |
| Shipping Weight – w/o fuel – lb (kg) | 9740 (4418) | |
| Working Weight – w fuel – lb (kg) | 10765 (4883) | |

Key Features

- Enclosure design includes gull wing doors, drop down tailgate doors and a cooler access hatch to provide the best servicing capabilities in the industry.
- The efficient central drain system allows operators to easily drain fluids from the radiator and oil and fuel tanks to a central location, without having to crawl under the machine.
- Operation is made easy and efficient with a control panel that offers more detail and preloaded resources than any other control panel in the market.
- Equipped with a Doosan-designed and manufactured airend that offers a highly efficient rotor profile, requiring less horsepower to deliver high-volume cfm output.
- Built to excel in rugged conditions with a heavy-gauge steel enclosure, heavy-duty tandem-axle running gear and construction-grade pedestal jack stand.
- Available with IQ System® that provides Instrument Quality air.

