



G125WCU-3A-T4F MOBILE GENERATOR

AVAILABLE FOR
RENT OR SALE



www.atsequipment.com

EPA COMPLIANT MOBILE GENERATOR

Doosan mobile generators produce a broad range of output voltages thanks to the standard three-position voltage selector switch or link board panel. The voltage change feature is protected from unauthorized access and will shut the machine down to prevent switching during operation. The customer connection panel is spacious and designed to accept a wide variety of power cables. The convenience receptacle panel includes 240V single phase twist-lock receptacles and 120V GFCI receptacles that are powered any time the unit is running.



The G125-150 models include the upgraded CoolBox Plus™ enclosure design which adds a temperature-controlled, variable-speed cooling fan to the package. This allows enhanced performance in extreme ambient temperatures while further improving sound attenuation and reducing water ingress across the operating range.

Doosan's advanced controls include an LCD display which annunciates any warnings or shutdowns. In addition, the controller logs all system faults, greatly aiding technicians with diagnostics. The system also supports remote auto start/stop control, plus integration with various telematics systems.

The G125-400 range is powered by Cummins tier 4-compliant diesel engines, paired with high capacity diesel exhaust fluid (DEF) tanks to ensure the DEF supply is matched to the available fuel supply.

PRIME POWER RATING

@ 480V-3Ø, 0.8PF, 60Hz	235 kVA (188 kW), 283 Amps
@ 240V-3Ø, 0.8PF, 60Hz	235 kVA (188 kW), 566 Amps
@ 208V-3Ø, 0.8PF, 60Hz	219 kVA (175 kW), 608 Amps
@ 240V-1Ø, 1.0PF, 60Hz	136 kVA (136 kW), 567 Amps
@ 120V-1Ø, 1.0PF, 60Hz	136 kVA (136 kW), 567 x 2 Amps
@ 400V-3Ø, 0.8PF, 50Hz	200 kVA (160 kW), 289 Amps

Voltage Configuration Link Board Panel

Frequency Capability 50Hz/60Hz Switchable

ENGINE

Engine Make / Model Cummins QSB7-G9

Displacement (L) 6.7

Number of Cylinders 6

Power Output @ 1800RPM - HP (kWm) 282 (210)

Power Output @ 1800RPM - HP (kWm) 282 (210)

Emissions Tier Level Tier 4 Final

Aftertreatment Technology DOC / SCR

Fuel Tank Capacity - Gal (L) 330 (1249)

Diesel Exhaust Fluid (DEF) Capacity - Gal (L) 24.4 (92.4)

Runtime @ 100% Load - Hr 24.4

DIMENSIONS WITH RUNNING GEAR

Length - in (mm) 224 (5689)

Width - in (mm) 83.2 (2114)

Height - in (mm) 102.9 (2615)

Weight (Ready to Run) - lb (kg) 11377 (5172)

Sound Level @ 23 ft (7m) and 100% Load - dB(A) 69

ATS EQUIPMENT INC. Construction Equipment & Supplies Rentals • Sales • Service

BOSTON, MA
(617) 825-3600

AUBURN, MA
(508) 832-8500

REHOBOTH, MA
(508) 379-6200

CANDIA, NH
(603) 483-2100