heat wagon portable space vented heaters



www.atsequipment.com

heat wagon 🍃

1800L Liquid Propane

SPECIFICATIONS

Input......750,000 BTU/Hr

Fuel.....Liquid Propane

Inlet Pressure......Max PS.. Min PSI

Liquid Propane......350 lbs.. 5 lbs.

Manifold Pressure......Propane 7.0" w.c.

Gas Consumption......8.2 GPH

Gas Connection......1/4" FNPT

Electrical Requirements......120 Volts 20 amp circuit

Thermostat.....Standard On/Off

Temp Rise......385°F

Dimension......50"L x 26"W x 30"H

Approximate Weight......200 lbs.

Features

- Air flow switch
- Burner heat shield
- Dual fuel
- Ductable
- Flame safeguard control
- Hi limit switch
- Manifold pressure gauge
- Motor overload manual reset
- Panel mounted thermostat
- Panel mounted voltage meter
- Weather sealed control box

Benefits

- Safe fuel shutdown if combustion air is interrupted
- Low housing temperature
- Simple lever change from propane to natural gas
- May be ducted up to 50 feet
- Safe monitoring of combustion, two trial electronic ignition with 20 second pre-purge time delay and 7 second shutdown
- Protects heater by shutting down if unit is being overfired
- Helps in diagnosing specific gas flow problems
- Protects heater by shutting down if voltage is too low
- Automatically cycles the heater on/off with a 10 second fan shutdown delay
- Easy monitoring of supply voltage to ensure trouble-free operation
- Indoor/outdoor usage

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals · Sales · Service

BOSTON, MA (617) 825-3600 AUBURN, MA (508) 832-8500

REHOBOTH, MA (508) 379-6200

CANDIA, NH (603) 483-2100