

Kerosene Forced Air

Our kerosene-fired forced air heaters are ideal for commercial, industrial and agricultural applications. Portable and easy to operate, these units extend heat to wide areas creating a comfortable environment even in the harshest conditions.



Limited Warranty:
1 Year



Important Notes:
 - Not for use in residential living areas or inadequately ventilated areas
 - Proper ventilation required during operation
 - Must be plugged into an approved standard electrical outlet for operation



MH-0070-0M10

Motor

✓ Heavy-duty, high quality cast aluminum enclosed electric motor

Burner Head

✓ 1-piece cast aluminum

Components

- ✓ High performance fan
- ✓ Built-in temperature control thermostat with control dial
- ✓ Integral overheat and flame-out safety
- ✓ Fuel gauge
- ✓ Sure start ignition for cold temperature starts
- ✓ Dual connector ignitor

For use in workshops, warehouses, garages, construction sites and farms with proper ventilation.

Factory tested for multiple fuels:

- Kerosene
- JP8/Jet A fuel
- No. 1 and No. 2 fuel oil
- No. 1 and No. 2 diesel fuel

To see more online, scan here or go to www.mitm.com:



MODEL NUMBER	MH-0070-0M10	MH-0125-0M10	MH-0175-0M10	MH-0215-0M10	MH-0400-0M10	MH-0600-0M10
HEAT OUTPUT	70,000 BTU	125,000 BTU	175,000 BTU	215,000 BTU	400,000 BTU	600,000 BTU
HOT-AIR FLOW	240 CFM	540 CFM	630 CFM	670 CFM	1,400 CFM	3,000 CFM
AIR PUMP PRESSURE	4.0 PSI	5.0 PSI	7.5 PSI	9.0 PSI	125 PSI	128 PSI
AC POWER	120V, 60Hz, 1.5 Amps	120V, 60Hz, 2.3 Amps	120V, 60Hz, 2.7 Amps	120V, 60Hz, 2.8 Amps	120V, 60Hz, 3.0 Amps	120V, 60Hz, 5.5 Amps
MOTOR SIZE	1/8 HP	1/5 HP	1/4 HP	1/3 HP	1/2 HP	5/8 HP
FUEL TANK CAPACITY	5.0 gallons	10.0 gallons	13.0 gallons	13.0 gallons	24.0 gallons	40.0 gallons
FUEL CONSUMPTION	0.53 gal./hr.	0.95 gal./hr.	1.34 gal./hr.	1.63 gal./hr.	3.00 gal./hr.	4.5 gal./hr.
MAX. OPERATING HOURS	9.4 hours	10.5 hours	9.7 hours	8.0 hours	8.0 hours	8.9 hours
HEATING AREA	1,700 sq. ft.	3,100 sq. ft.	4,300 sq. ft.	5,300 sq. ft.	10,000 sq. ft.	15,000 sq. ft.
MULTI-FUEL CAPABLE	Yes	Yes	Yes	Yes	Yes	Yes
DIGITAL TEMP. READ-OUT	No	Yes	Yes	Yes	No	No
ERROR INDICATOR READ-OUT	No	Yes	Yes	Yes	Yes	Yes
PARTS STORAGE SYSTEM	No	Yes	Yes	Yes	Yes	Yes
DIMENSIONS (LxWxH)	30x13x15in.	37x22x25in.	42x24x26in.	42x24x26in.	53x30x36in.	75x34x43in.
SHIP WT.	33 lb.	57 lb.	65 lb.	68 lb.	159 lb.	376 lb.
NET WT.	28 lb.	51 lb.	58 lb.	61 lb.	150 lb.	320 lb.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances. Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.