

Propane Tank-Top Radiant

For convenient, versatile radiant heat, these propane tank-top heaters are great for outdoor use. Just connect to a standard 20 pound propane cylinder for up to 48 hours of heating.

Limited Warranty:

1 Year



Important Notes:

- Not for use in residential living areas or inadequately ventilated areas
- Proper ventilation required during operation



MH-0030-IM10

Frame

- ✓ Heavy-duty construction
- ✓ Rust-proof chrome emitter guard
- ✓ Rear burner safety guard

Heat Output

- ✓ Variable heat control valve
- ✓ Clean, quiet, instant radiant heat

Components

- ✓ Standard propane tank connection
- ✓ High efficiency heat reflector
- ✓ Hand wheel connection for valve

For use in open workshops, construction sites, farms and for any other outdoor heating need.

MODEL NUMBER	MH-0015-IM10	MH-0030-IM10
HEAT OUTPUT (SINGLE BURNER)*	L-9,000 / M-12,000 / H-16,000 BTU	L-9,000 / M-12,000 / H-16,000 BTU
HEAT OUTPUT (DOUBLE BURNER)*	N/A	L-18,000 / M-24,000 / H-32,000 BTU
IGNITION TYPE	Match light	Match light
HEAT SETTINGS	3	6
PROPANE CYLINDER SIZE	20 lb.	20 lb.
MAX. OPERATING HOURS (20 LB. CYL)*	L-48 / M-36 / H-27 hours	L-48 / M-18 / H-14 hours
SWIVEL BURNER HEAD	No	Yes
SAFETY SHUT-OFF VALVE	Yes	Yes
HEAT REGULATOR KNOB	Yes	Yes
MANIFOLD	Cast aluminum	Cast aluminum
DIMENSIONS (LxWxH)	8.4x7.4x12in.	17.5x5.5x12in.
SHIP WT.	3 lb.	6 lb.
NET WT.	2 lb.	5 lb.

*Heat output and operating hours are at Low, Medium and High settings.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances.

Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

To see more online, scan here or go to www.mitm.com:

