

VOLT™

Electric Forced Air Portable Heaters

NEW



VOLT™	1.5	3	6	9	18-1	18-3	40	60
Wattage	1,500	3,000	6,000	9,000	19,000 (Full) 13,000 (Partial)	19,000 (Full) 13,000 (Partial)	40,000 (High) 32,000 (Medium) 16,000 (Low)	60,000 (High) 48,000 (Medium) 24,000 (Low)
BTU/H Rating	5,100	10,200	20,500	30,700	65,000 (Full) 45,000 (Partial)	65,000 (Full) 45,000 (Partial)	136,500 (high) 102,400 (medium) 51,200 (low)	205,000 (high) 164,000 (Medium) 82,000 (low)
Electric supply (volts/hz/phase)	120/60/1	240/60/1	240/60/1	240/60/1	240/60/1	240/60/3	480/60/3	480/60/3
Amps (Starting/Continuous Operation)	12.5	12.5	25	37.5	81 (full) 54 (Partial)	47 (full) 31 (Partial)	50 (High) 40 (Medium) 20 (Low)	75 (High) 60 (Medium) 30 (Low)
Blower Fan Output (CFM)	116	205	250	350	590 or 1,000	590 or 1,000	1,765	1,765
Power Cord	10ft, 12AWG	10ft, 16AWG	10ft, 8AWG	10ft, 8AWG	Not included	Not included	Not included	Not included
Max Cable Length	N/A	N/A	100-ft (8AWG, 3-wire, SOOW)	50-ft (8AWG, 3-wire, SOOW) 100-ft (6AWG, 3-wire, SOOW)	50-ft (2AWG, 3-wire, SOOW)	50-ft (6AWG, 4-wire, SOOW) 100-ft (4AWG, 4-wire, SOOW)	50-ft (4AWG, 4-wire, SOOW) 100-ft (2AWG, 4-wire, SOOW)	50-ft (2AWG, 4-wire, SOOW)
Plug	NEMA 5-15P	NEMA 6-15P	NEMA 14- 30P	NEMA 14-50P	Not included	Not included	Not included	Not included
Ambient Thermostat Temperature Range	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F
Length (in.)	11	11	20	23	32	32	46	46
Width (in.)	12	10	12	14	14	14	20	20
Height (in.)	8	15	17	18	20	20	25	25
Unit Weight (lbs.)	13.7	20.3	32.9	39.9	62	62	125	125
Shipping Weight (lbs.)	15	22	40	42	65	65	130	130
Running Decibels (dba)	47	50	55	55	58	58	82	82
Three Heat Output Modes	-	-	-	-	S	S	S	S
Powder Coated Steel Housing	S	S	S	S	S	S	S	S
Wheels	-	-	-	-	-	-	S	S
UL Approved	S	S	S	S	S	S	S	-

S=Standard

CA RESIDENTS:



WARNING

Cancer and reproductive harm. See www.P65Warnings.ca.gov.

INNOVATIVE HEATING SOLUTIONS

411 Mason Street, Onalaska, WI 54650
 (800) 345 7200
 (608) 783 5691
 (608) 783 6115, fax
 www.lbwhite.com
 Revised: 2/9/2022

© 2022 L.B. White Co.
 All rights reserved.
 All specifications are subject
 to change without notice.