



HB2200

AVAILABLE FOR
RENT OR SALE



www.atsequipment.com

SOLID BODY HYDRAULIC BREAKER

These heavy breakers are highly adapted for primary blast-free rock excavation and secondary rock breaking on construction sites and in quarries, surface and underground mines as well as primary demolition of massive reinforced concrete structures.

- **DustProtector optional**
- **Intelligent Protection System (IPS)**
- **VibroSilenced Plus**



^ TECHNICAL SPECIFICATIONS

Carrier weight class ¹	48 500 lb - 84 000 lb
Service weight ²	4 400 lb
Working tool diameter	5,71 inch
Working length of tool	25 inch
Hydraulic input power, max	76,4 HP
Oil flow	39,6 gpm - 50,2 gpm
Operating pressure	2 320 psi - 2 610 psi
Impact rate	300 blows/min - 625 blows/min
Sound power level, guaranteed ³	120 dB(A)

¹ Weights apply to standard carriers only. Any variances must be agreed with Epiroc and/or the carrier manufacturer prior to attachment.

² Attachment with standard working tool & average-sized adapter plate.

³ EN ISO 3744 in accordance with directive 2000/14/EC

ATS EQUIPMENT INC. Construction Equipment & Supplies Rentals • Sales • Service

BOSTON, MA
(617) 825-3600

AUBURN, MA
(508) 832-8500

REHOBOTH, MA
(508) 379-6200

CANDIA, NH
(603) 483-2100