

Epiroc
SB452

**AVAILABLE FOR
RENT OR SALE**



www.atsequipment.com

SOLID BODY HYDRAULIC BREAKER

Solid body breakers are perfect for demolishing light concrete structures and asphalt pavements, both outdoors and indoors, performing earthworks, scaling in underground operations, and cleaning ladles and converters in foundries.

- **Integrated percussion mechanism and guide system**
- **Designed without side bolts for maximum reliability**
- **Compact design for easy positioning**
- **Lower vibration and less noise**
- **Few parts and easy maintenance**



^ TECHNICAL SPECIFICATIONS

Carrier weight class ¹	14 300 lb - 28 700 lb
Service weight ²	970 lb
Working tool diameter	3,74 inch
Working length of tool	18,5 inch
Hydraulic input power, max	33,5 HP
Oil flow	14,5 gpm - 26,4 gpm
Operating pressure	1 450 psi - 2 175 psi
Impact rate	550 blows/min - 1 250 blows/min
Sound power level, guaranteed ³	122 dB(A)

¹ Weights apply to standard carriers only. Any variances must be agreed with Epiroc and/or the carrier manufacturer prior to attachment.

² Attachment with standard working tool & average-sized adapter plate.

³ EN ISO 3744 in accordance with directive 2000/14/EC

ATS EQUIPMENT INC. Construction Equipment & Supplies Rentals • Sales • Service

BOSTON, MA
(617) 825-3600

AUBURN, MA
(508) 832-8500

REHOBOTH, MA
(508) 379-6200

CANDIA, NH
(603) 483-2100