

Epiroc SB52

AVAILABLE FOR
RENT OR SALE

ATS
EQUIPMENT INC.

www.atsequipment.com

SOLID BODY HYDRAULIC BREAKER

Solid Body Breakers are perfect for demolishing light concrete structures and asphalt pavements, both outdoors and indoors, performing earthworks, scaling in underground operations, and cleaning ladles and converters in foundries.

- **Optional ContiLube (TM) II micro**
- **The integrated pressure relief valve protects against overloads**
- **Floating fit tool bushing with a patented tool locking system enables quick and easy on-site replacement**



^ TECHNICAL SPECIFICATIONS

Carrier weight class ¹	1 550 lb - 2 400 lb
Service weight ²	120 lb
Working tool diameter	1,57 inch
Working length of tool	10 inch
Hydraulic input power, max	9,1 HP
Oil flow	3,2 gpm - 7,1 gpm
Operating pressure	1 450 psi - 2 175 psi
Impact rate	750 blows/min - 1 700 blows/min
Sound power level, guaranteed ³	117 dB(A)

¹ Weights apply to standard carriers only. Any variances must be agreed with Epiroc and/or the carrier manufacturer prior to attachment.

² Attachment with standard working tool & average-sized adapter plate.

³ EN ISO 3744 in accordance with directive 2000/14/EC

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals • Sales • Service

BOSTON, MA
(617) 825-3600

AUBURN, MA
(508) 832-8500

REHOBOTH, MA
(508) 379-6200

CANDIA, NH
(603) 483-2100