

Epiroc SB552

**AVAILABLE FOR
RENT OR SALE**

**ATS
EQUIPMENT INC.**

www.atsequipment.com

SOLID BODY HYDRAULIC BREAKER

Choose an SB hydraulic breaker as your partner for a huge range of tasks. Suitable for most carriers like excavators, backhoe and skid steer loaders as well as demolition robots, it will get the job done – quickly and economically!

- Integrated percussion mechanism and guide system
- Designed without side bolts for maximum reliability
- Compact design for easy positioning
- Lower vibration and less noise
- Few parts and easy maintenance



^ TECHNICAL SPECIFICATIONS

Carrier weight class ¹	19 800 lb - 33 000 lb
Service weight ²	1 150 lb
Working tool diameter	3,94 inch
Working length of tool	19,5 inch
Hydraulic input power, max	38,6 HP
Oil flow	17,2 gpm - 30,4 gpm
Operating pressure	1 450 psi - 2 175 psi
Impact rate	650 blows/min - 1 150 blows/min
Sound power level, guaranteed ³	126 dB(A)

¹ Weights apply to standard carriers only. Any variances must be agreed with Epiroc and/or the carrier manufacturer prior to attachment.

² Attachment with standard working tool & average-sized adapter plate.

³ EN ISO 3744 in accordance with directive 2000/14/EC

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals • Sales • Service

**BOSTON, MA
(617) 825-3600**

**AUBURN, MA
(508) 832-8500**

**REHOBOTH, MA
(508) 379-6200**

**CANDIA, NH
(603) 483-2100**