

AVAILABLE FOR
RENT OR SALE

ATS
EQUIPMENT INC.

www.atsequipment.com

Epiroc

SB220

SOLID BODY HYDRAULIC BREAKER

SBU breakers are used for road work, trenching and demolition as well as in primary and secondary rock breaking. It has an air injection porting for under water breaking. A solid body breaker manufactured from a single block of cast metal.

- Integrated percussion mechanism and guide system
- Designed without side bolts for maximum reliability
- Compact design for easy positioning
- Lower vibration and less noise
- Few parts and easy maintenance



^ TECHNICAL SPECIFICATIONS

Carrier weight class ¹	6 170 lb - 13 225 lb
Service weight ²	494 lb
Working tool diameter	2,56 inch
Working length of tool	13 inch
Hydraulic input power, max	25,5 HP
Oil flow	11 gpm - 20 gpm
Operating pressure	1 450 psi - 2 175 psi
Impact rate	750 blows/min - 1 400 blows/min
Sound power level, guaranteed ³	118 dB(A)

¹ Weights apply to standard carriers only. Any variances must be agreed with Epiroc and/or the carrier manufacturer prior to attachment.

² Attachment with standard working tool & average-sized adapter plate.

³ EN ISO 3744 in accordance with directive 2000/14/EC

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals • Sales • Service

BOSTON, MA
(617) 825-3600

AUBURN, MA
(508) 832-8500

REHOBOTH, MA
(508) 379-6200

CANDIA, NH
(603) 483-2100