



HB3100

AVAILABLE FOR
RENT OR SALE



www.atsequipment.com

SOLID BODY HYDRAULIC BREAKER

Choose our hydraulic breakers as your partner for a huge range of tasks. Suitable for a wide range of carriers like wheeled and crawler excavators will get the job done – quickly and economically!

- DustProtector optional
- ContiLube® II
- Intelligent Protection System (IPS)



^ TECHNICAL SPECIFICATIONS

Carrier weight class ¹	70 500 lb - 115 000 lb
Service weight ²	6 800 lb
Working tool diameter	6,5 inch
Working length of tool	27 inch
Hydraulic input power, max	108,6 HP
Oil flow	55,5 gpm - 71,3 gpm
Operating pressure	2 320 psi - 2 610 psi
Impact rate	280 blows/min - 560 blows/min
Sound power level, guaranteed ³	120 dB(A)

¹ Weights apply to standard carriers only. Any variances must be agreed with Epiroc and/or the carrier manufacturer prior to attachment.

² Attachment with standard working tool & average-sized adapter plate.

³ EN ISO 3744 in accordance with directive 2000/14/EC

ATS EQUIPMENT INC.

Construction Equipment & Supplies

Rentals • Sales • Service

BOSTON, MA
(617) 825-3600

AUBURN, MA
(508) 832-8500

REHOBOTH, MA
(508) 379-6200

CANDIA, NH
(603) 483-2100